


# EM300-ZLD

## Zone Leak Detection Sensor



EM300-ZLD is a compact zone leakage detection sensor for detecting large area presence of water (or other liquids) and transmitting alarm using LoRaWAN® technology. With this low power consumption technology, EM300-ZLD can work up to 5 years with 4000 mAh battery. Combining with Milesight LoRaWAN® gateway and Milesight IoT Cloud solution, users can manage all sensor data remotely and visually and receive alarms via mobile APP.

EM300-ZLD also integrates temperature and humidity sensors, which has a great use for applications such as pipe leakage monitoring, basement flooding, pump failure, etc.

### ◆ Features

- Detect the presence of liquids by a long cable and based on the conductive principle
- Embedded with temperature and humidity sensors for environment monitoring
- Ultra-wide-distance transmission up to line of sight of 10km
- IP67 UV-resistant and waterproof enclosure for harsh environment applications
- Built-in 4000 mAh replaceable battery and works for 5 years without replacement
- Equipped with NFC for easily configuration
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Milesight IoT Cloud solution

## ◆ Specifications

<b>Wireless Transmission</b>	
Technology	LoRaWAN®
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)
Sensitivity	-147dBm @300bps
Mode	OTAA/ABP Class A
<b>Measurement</b>	
<b>Leakage Detection</b>	
Trigger Condition	When liquid level reaches 5mm
Detection Cable	3m (customizable)
<b>Temperature</b>	
Range	-30°C to + 70°C
Accuracy	0°C to + 70°C (+/- 0.3°C), -30°C to 0°C (+/- 0.6°C)
Resolution	0.1°C
<b>Humidity</b>	
Range	0% to 100% RH
Accuracy	10% to 90% RH (+/- 3%), below 10% and above 90% RH (+/- 5%)
Resolution	0.5% RH
<b>Operation</b>	
Power On & Off	NFC, power button (Internal)
Configuration	Mobile APP(via NFC) or PC software (via USB Type-C)
<b>Physical Characteristics</b>	
Power Supply	1 × 4000 mAh ER18505 Li-SOCL <sub>2</sub> battery (extendable to 2 batteries)
Battery Life*	>5 years (10 min interval and alarm once every day, SF10)
Operating Temperature	-30°C to +70°C
Relative Humidity	0% to 100% (non-condensing)
Ingress Protection	IP67
Dimension	105.6 × 85.3 × 27 mm (4.16 × 3.36 × 1.06 in)
Installation	Wall Mounting

\* Tested under laboratory conditions and for guideline purposes only.

Xiamen Milesight IoT Co., Ltd.

4/F, No.63-2 Wanghai Road, 2<sup>nd</sup> Software Park Xiamen 361008, China

Phone: +86-0592-5085280 Website: [www.milesight-iot.com](http://www.milesight-iot.com)

Fax: +86-0592-5023065 Email: [iot.sales@milesight.com](mailto:iot.sales@milesight.com)

